

STRUCTURAL INTEGRITY ASSESSMENT OF WELDED BUCKET-WHEEL BOOM PROCENA INTEGRITETA KONSTRUKCIJE STRELE ODLAGAČA ROTORNOG BAGERA

Originalni naučni rad / Original scientific paper
UDK /UDC:

Rad primljen / Paper received: 10.10.2021

Adresa autora / Author's address:

¹) Institute for Materials Testing, Belgrade, Serbia

²) University of Belgrade, Faculty of Mechanical Engineering, Serbia email: asedmak@mas.bg.ac.rs

³) University of Belgrade, Innovation Centre of the Faculty of Mechanical Engineering, Belgrade, Serbia, email: simon.sedmak@yahoo.com

Keywords

- bucket-wheel boom
- damage
- structural integrity assessment
- repair

Abstract

Research is conducted on the causes of damage and the structural integrity assessment of the bucket-wheel boom welded lattice structures, before and after the repair of vital structures. Additionally, the paper describes the investigation conducted based on the results of non-destructive tests (visual-, magnetic particle-, dye penetrant-, and ultrasonic tests), results of tensometric measurements that refer to the stress-strain state, and results based on numerical calculation of stresses by finite element method, performed through the use of a 3D model in the software Radimpex Tower 6.0[®]. The results of tests and research performed after the repair of damaged structural welded sections show that the integrity of the lattice structure of the bucket-wheel boom is not in danger when being properly handled and when the operational procedures are being obeyed.

INTRODUCTION

There are 2 bucket-wheel excavators at the coal landfill of thermal power plant 'Nikola Tesla A' in Obrenovac (Serbia), DU1 and DU2, produced in France /1/. These bucket-wheel excavators move along the circular track (widely known as polar track). Non-destructive tests (visual-, magnetic particle-, dye penetrant-, and ultrasonic tests) and tensometric measurements of strains are performed in order to analyse causes of the occurrence of damage on welded sections of the bucket-wheel boom of excavator DU1 and evaluate its integrity after the execution of repairs.

Taking into account the long period of operation under severe working conditions (dynamic loading with changeable amplitudes), and the fact that during their design there were practically no possibilities to carry out detailed stress-strain analysis, the highly loaded elements and their joints had to be checked discretely or continuously /2-11/. This especially refers to welded joints and welded structures, /2, 3, 6, 7/.

The quality of welded joints and the integrity of welded structures depend on a large number of technological and metallurgical factors (form of welded joint, stress concentration, heterogeneity of structural and mechanical properties of parent material, heat-affected zone and weld metal, residual stresses and strains that occur due to welding and the

Ključne reči

- strela odlagača rotornog bagera
- oštećenje
- procena integriteta konstrukcije
- reparacija

Izvod

Obavljena istraživanja obuhvataju uzroke oštećenja i procenu integriteta zavarene rešetkaste konstrukcije strele odlagača rotornog bagera, pre i posle reparacije vitalnih delova konstrukcije. Osim toga, u radu je predstavljeno istraživanje obavljeno na osnovu rezultata ispitivanja bez razaranja (vizuelno, magnetnim česticama, penetrantima i ultrazvučno ispitivanje), zatim na osnovu rezultata tenzometrijskih merenja stanja napon-deformacija, kao i na bazi rezultata numeričkog proračuna napona metodom konačnih elemenata, izvedenog primenom 3D modela u softveru Radimpex Tower 6.0[®]. Rezultati ispitivanja, kao i istraživanja izvedena posle reparacije oštećenih delova zavarene rešetkaste konstrukcije pokazuju da nema opasnosti za integritet rešetkaste konstrukcije strele rotornog bagera, ako se pravilno rukuje i ako se poštuju postupci u radnim uslovima.

existence of defects within welded joints), while the integrity of welded structures, apart from technological and metallurgical factors, also depends on structural and exploitative factors.

The paper contains the methodological approach to the analysis of causes of damage at vital components of welded lattice structures that are sections of the bucket-wheel boom, and the evaluation of its integrity after repair. Taking into account that the user of the excavator does not possess the project and technical documentation, all tests and research presented here are conducted under the assumption that welded lattice structures are made of structural steels of the type S355 and S235.

DAMAGE AT VITAL SECTIONS OF THE WELDED BUCKET-WHEEL BOOM

The presented damage is detected mainly through visual testing (VT) of parent material and welded joints. No other defects are detected through the use of other non-destructive testing methods, and no deviations from expected results had occurred during hardness tests. Locations of repaired welded joints are shown in Fig. 1. Sections of the vital structure in the upper zone of the bucket-wheel boom where defects were detected after repair are presented in Fig. 2.




Figure 1. Locations of repaired welded joints.



Figure 2. Sections on vital structure of bucket-wheel boom.

REPAIR OF VITAL WELDED STRUCTURES OF THE BUCKET-WHEEL BOOM

The repair of vital welded structures of the bucket-wheel excavator, designated DU1, is performed by fillet and butt welding of sheets and profiles of structural steel, executed by repairing damaged sections and/or embedding reinforcements, while applying previously defined welding technology, /12/.

Taking into account the fact that user of the equipment does not possess design and technical documentation, the welding technology is defined for structural steels S355 and S235, mostly being used for manufacturing steel structures on bucket-wheel excavators.

Chemical composition and tensile properties of structural steels S235 and S355 are presented in Tables 1 and 2, respectively.

Table 1. Chemical composition of steels S 235 and S 355, /13/.

Steel	C	Si	Mn	P	S	N
S 235	≤ 0.19	-	≤ 1.50	≤ 0.045	≤ 0.045	≤ 0.009
S 355	≤ 0.23	≤ 0.60	≤ 1.70	≤ 0.045	≤ 0.045	≤ 0.009

Table 2. Mechanical properties of steels S 235 and S 355, /13/.

Steel	Yield stress, YS [N/mm ²]	Tensile strength, TS [N/mm ²]	Elongation, A ₅ [%]
S 235	240	370-450	25
S 355	355	520-620	22

Weldability of parent material

According to the IIW equation for chemical composition of sheets and profiles presented in Table 1, C_{eq} is lower than 0.40, which indicates that their weldability is good:

- for chemical composition of profile materials presented in Table 5 and taking into account the most unfavourable content of hydrogen in weld metal of $H = 6 \text{ ml}/100 \text{ g}$, it can be concluded that no preheating is necessary;
- maximum hardness in the heat-affected zone for presented chemical compositions should not be over 350 HV, the upper limit for material not to be prone to cold cracking;
- critical cooling rate at which purely martensitic structure, which may cause the occurrence of cold cracks, is created in the heat-affected zone, should be lower than $32 \text{ }^\circ\text{C}/\text{s}$. So, it is not necessary to predict lower cooling rates;
- if tensile strength of profile and sheet steels is lower than 700 MPa, there is no possibility of the occurrence of hot cracks.

Selection of the welding process and filler material

As the most suitable, the welding process 111 is used. Due to limited possibilities of the execution of preheating and post weld heat treatment, the optimum solution is to use electrodes with basic coating.

Surface cracks in parent material are eliminated by fine grinding, while in vital welded joint areas, surface welding is carried out after the elimination of cracks by using EVB 50 electrodes (Electrodes Jesenice, Slovenia), /14/. The

chemical composition of pure weld metal is defined in Table 3, while the mechanical properties are presented in Table 4.

Table 3. Chemical composition, values in [%].

Electrode	C	Si	Mn
EVB 50	0.08	0.60	1.0

Table 4. Mechanical properties of pure weld metal.

Electrode	Yield stress [N/mm ²]	Tensile strength TS [N/mm ²]	Elongation A ₅ [%]	Impact energy KV _{300/2} [J/cm ²]
EVB 50	> 440	510 – 610	> 24	47 (-20 °C)

STRESS STATE OF BUCKET-WHEEL BOOM VITAL STRUCTURES


The stress state of bucket-wheel boom vital structures is determined by finite element numerical calculation of stresses, performed through the use of a 3D model in software Radimpex Tower 6.0[®], and based on tensometric measurements of local deformations through the application of strain gauges.

Numerical calculation of stresses of bucket-wheel boom vital structures

Numerical calculation of stresses in vital structures of the bucket-wheel boom is carried out by the finite element method performed through the use of a 3D model in Radimpex Tower 6.0, which is a professional software for static and dynamic calculations, as well as for dimensioning all types of steel, concrete, and wooden structures. Maximal stress values calculated through Radimpex Tower 6.0 are presented in Tables 5 and 6.

Tensometric measurements and calculation of stresses in bucket-wheel boom vital structure

Measurement areas and locations on the vital lattice structure of bucket-wheel boom, as an integral part of excavator DU1 are presented in Figs. 3-4. Stress results as calculated based on measured strains are presented in Tables 5-7.






Figure 3. Measurement locations on the bucket-wheel boom shown in three different cross sections.

Table 5. Measured and calculated stresses in the vital structure of the bucket-wheel boom (Fig. 3a).

Loads on the bucket-wheel excavator DU1	Measurement locations at cross-section 0							
	M ₁	M ₂	M ₃	M ₄	M ₅	M ₆	M ₇	M ₈
Measured stress for boom position at 0°, MPa	-	-	15.2	16.0	32.8	32.4	31.2	31.2
Numerical stress for boom position at 0°, MPa	-	-	20.6	20.6	29	29	29	27.5
Measured stress for boom position at 12°30', MPa	-	-	28	19.0	21.2	22	19.2	17.2
Numerical stress for boom position at 12°30', MPa			20.4	20.4	28.7	28.7	28.7	27.3
Maximum stress for boom position at 0°, MPa	32.8							
Maximum stress for boom position at 12°30', MPa	28.7							

Table 6. Measured and calculated stresses in the vital structure of the bucket-wheel boom (Fig. 3b).

Loads on the bucket-wheel excavator DU1	Measurement locations at cross-section 0							
	M ₉	M ₁₀	M ₁₁	M ₁₂	M ₁₃	M ₁₄	M ₁₅	M ₁₆
Measured stress for boom position at 0°, MPa	32.8	27.6	31.2	30.8	28.4	27.2	30.0	29.6
Numerical stress for boom position at 0°, MPa	27.5	27.8	29.0	29.0	29.0	27.5	27.5	27.5
Measured stress for boom position at 12°30', MPa	20.4	18.0	20.0	19.2	18.0	19.2	16.8	16.4
Numerical stress for boom position at 12°30', MPa	27.3	27.3	28.7	28.7	28.7	27.3	27.3	27.3
Maximum stress for boom position at 0°, MPa	32.8							
Maximum stress for boom position at 12°30', MPa	20.4							

Table 7. Measured and calculated stresses in the vital structure of the bucket-wheel boom (Fig. 3c).

Loads at the bucket-wheel excavator DU1	Measurement locations at cross-section 11					
	M ₁₇	M ₁₈	M ₁₉	M ₂₀	M ₂₁	M ₂₂
Measured stress for boom position at 0°, MPa	41.2	44.4	44.4	41.2	20.4	20.4
Numerical stress for boom position at 0°, MPa	36.4	36.4	38.6	38.6	44.0	44.0
Measured stress for boom position at 12°30', MPa	31.2	31.2	30.0	30.4	12.0	12.4
Numerical stress for boom position at 12°30', MPa	36.0	36.0	38.3	38.3	44.0	44.0
Maximum stress for boom position at 0°, MPa	44.4					
Maximum stress for boom position at 12°30', MPa	30.4					

INTEGRITY ASSESSMENT OF BUCKET-WHEEL BOOM VITAL SECTIONS

Regarding the analysis of damages that occurred at vital sections of welded lattice structures in the bucket-wheel boom, the technical diagnostics should be based on predetermined procedures which refer to non-destructive testing, history of their application taking into account expert knowledge that relates to similar structures and conditions of exploitation of bucket-wheel excavators.

Structural integrity a relatively recent scientific and engineering discipline which in a broader sense comprises the state analysis and technical diagnostics that refers to structural behaviour, revitalization of structures and service life evaluation. Apart from the usual procedure for structural integrity assessment, when defects are detected through application of non-destructive tests, this discipline also comprises the stress state analysis in the defectless structure. This procedure enables plotting of stress-strain states, which

helps identification of weak spots in analysed components of supporting structures, even before defects occur.

Bases on the results of executed non-destructive tests; numerical calculation and stress state determination through tensometric measurements before and after repair of vital sections of welded structures of the bucket-wheel boom where damages had occurred, it was determined that the integrity of the bucket-wheel boom is not compromised if there are no cracks and other defects within welded joints,

as well as when bucket-wheel excavators are properly handled and work procedures are respected. However, the bucket-wheel boom is compromised when excessive loading occurs due to improper manipulation by the operator of the bucket-wheel excavator, or from the influence of extremely strong winds.

Significant presence of defects is caused by a complex geometry, due to the fact that those areas are nodal spots that are principally critical in lattice structures, Fig. 4.




Figure 4. Locations of welded joints in which fatigue cracks mainly occur, /15/.

CONCLUSIONS

Since the maximum measured working stress (44.4 MPa) is much smaller than the stress that would cause any damage in the bucket wheel boom, including welded joints, one can conclude that the detected damage occurred as a result of manufacturing defects.

Presented results emphasize the importance of execution of non-destructive tests on welded joints of vital structural sections not only during the manufacture, but also during exploitation.

ACKNOWLEDGEMENTS

This work is supported by the Ministry of Education, Science and Technological Development of the Republic of Serbia (Contract No. 451-03-9/2021-14/200012, 451-03-68/2020-14/200135, and 451-03-68/2020-14/200213).

REFERENCES

1. Documentation regarding bucket-wheel excavators DU1 and DU2 at the open pit surface mine, Thermal Power Plant 'Nikola Tesla A' at Obrenovac, manufactured by 'Ameco', France.
2. Sedmak S., Sedmak, A., Arsić, M., Vojvodić Tuma, J. (2007), *An experimental verification of numerical models for the fracture and fatigue of welded structures*, Mater. Technol. 41(4): 173-178.
3. Arsić, M., Mladenović, M., Veljović, A., et al. (2009), *Reliability of critical welded joints in responsible support structures of bucket wheel excavator*, XIX Int. Conf. on Material Handling, Constructions and Logistics - MHCL'09, Belgrade, pp.133-138.
4. Bošnjak, S., Zrnić, N., Simonović, A., Momčilović, D. (2009), *Failure analysis of the end eye connection of the bucket wheel excavator portal tie-rod support*, Eng. Fail. Anal. 16(3): 740-750. doi: 10.1016/j.engfailanal.2008.06.006
5. Rusiński, E., Czmochoowski, J., Iluk, A., Kowalczyk, M. (2010), *An analysis of the causes of a BWE counterweight boom support fracture*, Eng. Fail. Anal. 17(1): 179-191. doi: 10.1016/j.engfailanal.2009.06.001

6. Arsić, M., Bošnjak, S., Zrnić, N., et al. (2011), *Bucket wheel failure caused by residual stresses in welded joints*, Eng. Fail. Anal. 18(2): 700-712. doi: 10.1016/j.engfailanal.2010.11.009
7. Bošnjak, S., Arsić, M., Zrnić, N., et al. (2011), *Bucket wheel excavator: Integrity assessment of the bucket wheel boom tie-rod welded joint*, Engineering Failure Analysis, 18(1): 212-222. doi: 10.1016/j.engfailanal.2010.09.001
8. Daničić, D., Sedmak, S., Blačić, I., Kirin, S. (2013), *Scenario of fracture development in bucket wheel excavator*, Struct. Integ. and Life, 13(3): 189-196.
9. Kirin, S., Stanojević, P., Miljanović, I., et al. (2015), *Influence of the human factor on risks in an open-pit mine*, Struct. Integ. and Life, 15(2): 117-128.
10. Bošnjak, S., Petković, Z., Matejić, P., et al. (2005), *Analysis of stress-strain state of bucket wheel excavator revolving platform structure - fundament of efficient reconstruction*, Struct. Integ. and Life, 5(3): 129-142.
11. Arsić, D., Gnjatović, N., Simon, S., et al. (2019), *Integrity assessment and determination of residual fatigue life of vital parts of bucket-wheel excavator operating under dynamic loads*, Eng. Fail. Anal. 105: 182-195. doi: 10.1016/j.engfailanal.2019.06.072
12. Arsić, M., Welding technology for structural steel components of bucket-wheel excavator boom 'DU1' and 'DU2' placed at coal bed mine of 'Nikola Tesla A' Thermal Power Plant (in Serbian: *Tehnologija zavarivanja delova čelične konstrukcije strele rotora bagera 'DU1' i 'DU2' na deponiji uglja termoelektrane 'Nikola Tesla A'*), Institute for Materials Testing, Report No. MP-030010CM, Belgrade, 2010.
13. EN 10025-2: Hot rolled products of structural steels - Part 2: Technical delivery conditions for non-alloy structural steels, European Committee for Standardization, 2004.
14. EN 499: E 42 4 B 32 H5, Welding consumables. Covered electrodes for manual metal arc welding of non-alloy and fine grain steels. Classification, European Committee for Standardization, 1995.
15. Arsić, M., Flajs, Z., Sedmak, A., Veg, E., Sedmak, S. (2021), *Damage occurrence in welded structures of the bucket-wheel boom*, paper accepted for the 12th Int. Conf. 'Innovative Technologies for Joining Advanced Materials' TIMA 21, Nov. 25-26, 2021, Timisoara, Romania, Proceedings to be published by www.scientific.net

© 2021 The Author. Structural Integrity and Life, Published by DIVK (The Society for Structural Integrity and Life 'Prof. Dr Stojan Sedmak') (<http://divk.inovacionicentar.rs/ivk/home.html>). This is an open access article distributed under the terms and conditions of the [Creative Commons Attribution-NonCommercial-NoDerivatives 4.0 International License](https://creativecommons.org/licenses/by-nc-nd/4.0/)

2ND GLOBAL SUMMIT ON CIVIL, ARCHITECTURAL AND ENVIRONMENTAL ENGINEERING (GSCAEE2022)

June 16-18, 2022 in Copenhagen, Denmark

Organized by *The Scientistt*

The Scientistt

GSCAEE2022 aims to bring together the renowned researchers, scientists and scholars to exchange ideas, to present sophisticated research works and to discuss hot topics in the field and share their experiences on all aspects of Civil, Architectural and Environmental Engineering.

The GSCAEE2022 will be a 3 days event that means to gather the key players of the Civil, Architectural and Environmental Engineering community and related sectors. This event is launched with the aims to become an established event, attracting global participants, intent on sharing, exchanging and exploring new avenues of Civil, Architectural and Environmental Engineering related scientific and commercial developments.

A wide-ranging scientific program consisting of Plenary lectures, Keynote lectures, Invited lectures, Parallel sessions, as well as Poster sessions for young scientists covering all topics in Civil, Architectural and Environmental Engineering will be scheduled. This conference provides a wonderful opportunity for you to enhance your knowledge about the newest interdisciplinary approaches in Civil, Architectural and Environmental Engineering.

Moreover, the conference offers a valuable platform to create new contacts in the field of Civil, Architectural and Environmental Engineering, by providing valuable networking time for you to meet great personnel in the field.

Topics:

Architectural Design and Theories; Structural Engineering; Civil and Urban Engineering; Concrete Structures; Environmental Engineering Aesthetics and Landscape Energy; Building Materials; Geotechnical Engineering; Hydraulic Engineering; Road and Bridge Engineering; Water Resources Engineering; Concrete Structure; Transportation System; Landscape Planning and Design; Coastal Engineering; Traditional & Advanced Construction Materials; Construction Market Research and Industry Analysis; Geology in Civil Engineering; Building Technology Science; Construction Technology; Environmental Engineering; Environment and Climate Change Intelligent Transportation and Logistics; Planning for Risk

and Natural Hazards; Steel Structures and Construction; Materials Science; Architectural Environment and Equipment Engineering; Environment-Friendly Construction and Development; Quality Management; Design-Build Contracts; Earth and Atmospheric Sciences; Marine Structures; Constructional Steel Research; Infrastructure in the Mining Industry

links

<https://www.thescientistt.com/civil-structural-environmental-engineering/2022/>

Important dates

Conference Dates: June 16-18, 2022

Abstract Submission Deadline: November 30, 2021

Registrations

Early Registration Deadline: November 28, 2021

Standard Registration Deadline: November 30, 2021

Contact:

Conference Secretary GSCAEE2022

Tel: +91 779 983 5553

Email: gscace2022@thescientistt.com