

**Serbian Ceramic Society Conference
ADVANCED CERAMICS AND APPLICATION**

Organized by
Serbian Ceramic Society
&
Institute of Technical Sciences of SASA

PROGRAM AND THE BOOK OF ABSTRACTS

**Serbian Academy of Sciences and Arts, Knez Mihailova 35
May 10-11th, 2012, Belgrade, Serbia**

Book title: Serbian Ceramic Society Conference - ADVANCED CERAMICS AND APPLICATION: Program and the Book of Abstracts

Publisher:

Serbian Ceramic Society

Editors:

Prof. Dr. Vojislav Mitić

Dr. Nina Obradović

Dr. Lidija Mančić

Technical Editor:

Aleksandra Stojičić

Printing:

Serbian Academy of Sciences and Arts,
Knez Mihailova 35, Belgrade, Serbia

Format

Pop Lukina 15, Belgrade, Serbia

Edition:

70 copies

CIP - Каталогизација у публикацији
Народна библиотека Србије, Београд

666.3/.7(048)

66.017/.018(048)

SERBIAN Ceramic Society. Conference (1 ; 2012 ; Beograd)

Advanced Ceramics and Application : program and the book of abstracts / #[1st]
#Serbian Ceramic Society Conference, May 10-11th, 2012, Belgrade, Serbia ; organized
by Serbian Ceramic Society & Institute of Technical Science of SASA ; [editors Vojislav
Mitić, Nina Obradović, Lidija Mančić]. - Belgrade : Serbian Ceramic Society, 2012
(Belgrade : Serbian Academy of Sciences and Arts). - XII, 37 str. ; 29 cm

Tiraž 70.

ISBN 978-86-915627-0-0

1. Srpsko keramičko društvo (Beograd)

a) Керамика - Апстракти b) Наука о материјалима - Апстракти c) Наноматеријали
- Апстракти

COBISS.SR-ID 190546188

P02

Kinetics of Mechanically Activated TiO₂-based Oxides Followed by DTA

N. Obradović¹, V.P. Pavlović², S. Filipović¹, D. Kosanović¹, V.B. Pavlović¹

¹Institute of Technical Sciences of SASA, Knez Mihajlova 35/IV, 11000 Belgrade, Serbia,

²Faculty of Mechanical Engineering, Belgrade University, Kraljice Marije 16, 11000 Belgrade, Serbia

TiO₂-based materials are widely used in production of ceramic capacitors and semiconductors. The conventional method of ceramics synthesis relies on the solid-state reaction between TiO₂ and other compounds (BaCO₃, BaO, ZnO, MgO and SrCO₃) at high temperatures. During this reaction control of final stoichiometry and powder characteristics are difficult to maintain, because of the lack of the consistency in initial raw material's mixture and the existence of local inhomogeneities in reaction product which occur as a result of incomplete mixing and incomplete reaction of the constituents. In the most cases the sintering kinetics of these ceramics are determined by several parameters, including pressed powder density, material's particle size, sintering temperature, atmosphere etc. As a result, during thermal treatment mass transport by plastic flow, bulk diffusion, surface and volume diffusion, grain boundary diffusion, or a combination of these processes may occur. In order to produce nanocrystalline powders and improve the sintering kinetics, high energy mechanical activation can be employed among other methods.

DTA analyses indicated that the position of DTA exothermic peak assigned to the process of ceramics formation was shifted toward lower temperatures in activated samples. The distinction in that peak magnitude due to activation process was observed as well. These results pointed out an increase of the solid state reaction rate, due to activation process. It was concluded that mechanical activation provoked the acceleration of mass transport and enhanced the nucleation probability of a new phase, which caused the decrease of synthesis reaction temperature.

P03

The Influence of Mechanical Activation on Sintering Process of BaCO₃-SrCO₃-TiO₂ System

D. Kosanović¹, N. Obradović¹, M. Mitrić², V. Pavlović¹, M.M. Ristić³

¹Institute of Technical Sciences of SASA, Knez Mihailova 35/IV, 11000 Belgrade, Serbia, ²The Vinča Institute of Nuclear Sciences, Belgrade University, Condensed Matter Physics Laboratory, P.O. BOX 522, 11001 Belgrade, Serbia, ³Serbian Academy of Sciences and Arts, Knez Mihailova 35, 11000 Belgrade, Serbia

In this article the influence of mechanical activation on sintering process of barium-strontium-titanate ceramics has been investigated. Both non-activated and mixtures treated in planetary ball mill for 5, 10, 20, 40, 80 and 120 minutes were sintered at 1100-1400 °C for 2 hours in air atmosphere. The influence of mechanical activation on phase composition and crystal structure has been analyzed by XRD, while the effect of activation and sintering process on microstructure was investigated by scanning electron microscopy. It has been established that temperature of 1100 °C was too low to induce final sintering stage for the system. Electrical measurements have been conducted for the densest ceramics sintered at 1400 °C for 2 hours.